





ELGEF Plus Tapping saddle PE100
d40-63mm / SDR11 / Monobloc version / With gas-stop 0.2 - 5 bar

- 5 bar Gas (for pressures from **200 mbar to 5 bar**)
- With integrated cutter to tap live mains under pressure
- Gas-Stop System Pipelife Type S (GS 32/200 UE)
- **With overflow orifice**
- Set comes with Gas-Stop pre-assembled
- Installation instructions of Gas-Stop manufacturer are to be observed
- Complete with lower part
- 4 mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- O-ring-sealed screw cap



d	Do3	DN	Code	Weight
(mm)	(mm)	(mm)		(kg)
40	32	32	193 130 814	0.290
50	32	40	193 130 824	0.283
63	32	50	193 130 834	0.446



L	L4	Db	W	H	H4	max Volume	Suitable for
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(l/min)	
120	76	16	103	99	33	750	SDR Pipe 9-11
120	76	16	103	104	38	750	SDR Pipe 9-11
130	76	25	126	134	44	750	SDR Pipe 9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>