





SYGEF Standard Diaphragm valve type 605 With butt fusion spigot metric

Model:

- Material: PVDF
- Compact full plastic design without screws
- High flow rate
- Actuator housing with thread for easy maintenance
- Quick opening & closing times
- For easy installation and removal
- Market standard installation length

Option:

- Individual configuration of the valve



d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	Actuator	FKM Code	Weight (kg)	PTFE/ EPDM* Code
20	15	6	125	FC	185 605 162	0.37	185 605 132
20	15	6	125	FO	185 605 164	0.34	185 605 134
20	15	6	125	DA	185 605 165	0.35	185 605 135

D (mm)	D1_G (inch)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	H7 (mm)	L (mm)	L2 (mm)	e (mm)	M	Lift = Hx (mm)
65	1/4	43	89	14	12	46	30	42	124	25	1.9	M6	6
65	1/4	43	89	14	12	46	30	42	124	25	1.9	M6	6
65	1/4	43	89	14	12	46	30	42	124	25	1.9	M6	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>