



## PROGEF Standard Bend 45° SDR17.6

### Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- Production process: segment welded
- Segment-welded fittings have a pressure reduction factor of 0.8

| d    | PN    | Code               | Weight | L    | L1   | R    | e    |
|------|-------|--------------------|--------|------|------|------|------|
| (mm) | (bar) |                    | (kg)   | (mm) | (mm) | (mm) | (mm) |
| 355  | 4     | <b>727 158 549</b> | 21.000 | 520  | 300  | 533  | 20.1 |
| 400  | 4     | <b>727 158 550</b> | 28.100 | 548  | 300  | 600  | 22.7 |
| 450  | 4     | <b>727 158 551</b> | 37.400 | 580  | 300  | 675  | 25.5 |
| 500  | 4     | <b>727 158 552</b> | 52.600 | 665  | 350  | 750  | 28.4 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>