Data sheet

valid from: 6/24/26



Lug-style end installation butterfly valve type 243 PVC-C
DA (Double acting)
Flange standard metric

Model:

- Overall length according to EN 558, ISO 5752 (DN50 - 200 line 25, DN250 - 300 line 10)
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Control pressure supply through integrated NAMUR interface according VDI/VDE 3845 with 4.2 bar (60.9 psi)
- Control time 90°<) 1-2s
- For easy installation and removal
- Full plastic solution (actuator housing made of PP-GF)
- Visual position indicator

Option:

- Optional accessory: Valve-Integrated position feedback with limit switches (limit switches have to be ordered separately)
- Positioner RPC, RPC D, RPC PID
- Individual configuration of the valve

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d (mm)	Size (inch)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
63	2	50	10	**199 243 752**	1	3.499	**199 243 762**	1	3.499
75	2 ½	65	10	**199 243 753**	1	3.656	**199 243 763**	1	3.656
90	3	80	10	**199 243 754**	1	4.692	**199 243 764**	1	4.692
110	4	100	10	**199 243 755**	1	6.406	**199 243 765**	1	6.406
140	5	125	10	**199 243 756**	1	9.222	**199 243 766**	1	9.222



d (mm)	Hmax (mm)	Lmax (mm)	Wmax (mm)	U (mm)	V (mm)	H4 (mm)	V1 (mm)	Lg (mm)	D2 (mm)	Q1 (mm)	Q2 (mm)	d2	k (mm)	Y (mm)
63	338.1	183.5	165	90	133.3	23	78.8	44.7	160	40		M16	125	111
75	351.0	183.5	182	90	139.9	23	85.1	45.7	180	54	35	M16	145	111
90	362.8	183.5	210	90	145.6	23	91.2	48.7	195	67	50	M16	160	111
110	404.5	261.0	240	90	166.0	23	107.5	55.6	226	88	74	M16	180	131
140	433.7	261.0	272	90	180.0	23	122.7	63.5	258	113	97	M16	210	131



d (mm)	E (mm)	Y1 (mm)	M2 (mm)
63	119.5	15	91.75
75	119.5	15	91.75
90	119.5	15	91.75
110	141.5		130.50
140	141.5		130.50

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com