




ELGEF Plus Stop-off saddle with PE-adaptor PE100 d63-400mm / SDR11 / Maximum passage 50 mm

- 10 bar Gas / 16 bar Water
- Complete with lower part
- Supplied as Kit with PE-Stop-Off Adaptor
- PE Stop-Off insert
- 4 mm pin connectors
- Limited path fusion indicators
- For main dimension d63 and d75mm we recommend a maximum cutting diameter of $d = 39\text{mm}$
- * Topload: delivery without lower part for assembling as Top Load with tool no. 799.350.477; angle adaptor (799.350.340) for fusion cable required



L = length / Länge

	d (mm)	SDR	PN (bar)	DN (mm)	G (inch)	Code	Weight (kg)	L (mm)	SDR pipe
	63	11	16	50	2 3/4	193 149 237	0.606	165	9 - 11
	75	11	16	65	2 3/4	193 149 247	0.765	165	9 - 11
	90	11	16	80	2 3/4	193 149 257	0.696	165	9 - 11
	110	11	16	100	2 3/4	193 149 267	0.732	182	9 - 17.6
	125	11	16	100	2 3/4	193 149 277	0.785	165	9 - 17.6
	140	11	16	125	2 3/4	193 149 287	0.820	165	9 - 17.6
	160	11	16	150	2 3/4	193 149 297	0.772	182	9 - 17.6
	180	11	16	150	2 3/4	193 149 307	0.920	165	9 - 26
	200	11	16	200	2 3/4	193 149 317	0.913	165	9 - 26
	225	11	16	200	2 3/4	193 149 327	0.910	165	9 - 26
	250	11	16	250	2 3/4	193 149 337	0.936	165	9 - 26
*	280	11	16	250	2 3/4	193 149 347	0.920	165	9 - 26
*	315 - 350	11	16	300 - 350	2 3/4	193 149 357	0.660	165	9 - 33
*	400	11	16	400	2 3/4	193 149 377	0.920	165	9 - 33