


PP Eccentric Reducer (HTR)



Material	PP (polypropylene)
Colour	Grey
Standard	SR EN 1451-1
Application	Soil & waste discharge and ventilation inside buildings
Joining	Socket with EPDM sealing ring (factory-fitted)
Temperature	60 °C operating; up to 95 °C short-term; resistant down to -15 °C
Chemical resistance	pH 2 - pH 12
Linear expansion	0.12 mm/m·K
Service life	Minimum 50 years

Code	D1 (mm)	D (mm)	L (mm)	L1 (mm)	Lm (mm)	Packaging (pcs/box/pallet)
FPPRD040XX32IGR	40	32	95	44	36	40/480/3840
FPPRD050032XXIGR	50	32	103	46	36	25/300/2400
FPPRD050040XXIGRN	50	40	103	46	39	25/250/2000
FPE0054	75	50	128	65	44	20/1200
FPPRD110050XXIGRN	110	50	146	58	42	100/800
FPE0053	110	75	146	65	51	20/480
FPE0038	125	110	158	73	56	20/240
FPE0039	160	110	174	88	69	20/240
FPE0113	160	125	170	85	70	20/240

Dimensions in mm; symbols refer to the drawing above.

Packaging = pieces per carton / box / pallet, as listed in the manufacturer's range.