Data sheet

valid from: 3/27/26





Ball valve type 542 PP-H
With threaded socket (Rp) reinforced
With PTFE ball seal

Model:

- For easy installation and removal
- Ball seat PTFE/ red lever

Option:

- Individual configuration of the valve possible
- Assembling of a valve tag possible

d (mm)	DN (mm)	Thread Type	Size (inch)	PN (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	SP	Weight (kg)
16	10	Rp	⅜	10	71	**167 542 021**	1	0.120
20	15	Rp	½	10	185	**167 542 022**	1	0.130
25	20	Rp	¾	10	350	**167 542 023**	1	0.180
32	25	Rp	1	10	700	**167 542 024**	1	0.282
40	32	Rp	1 ¼	10	1000	**167 542 025**	1	0.460
50	40	Rp	1 ½	10	1600	**167 542 026**	1	0.635
63	50	Rp	2	10	3100	**167 542 027**	1	1.190

d (mm)	FKM Code	SP	Weight (kg)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	L5 (mm)	L6 (mm)	z (mm)
16	**167 542 031**	1	0.120	50	54	96	72	56	26	46	70
20	**167 542 032**	1	0.130	50	54	99	72	56	26	46	66
25	**167 542 033**	1	0.180	58	66	111	93	65	34	59	75
32	**167 542 034**	1	0.282	68	71	127	93	71	34	59	85
40	**167 542 035**	1	0.460	84	85	147	110	85	41	69	101
50	**167 542 036**	1	0.635	97	92	157	110	89	41	69	111
63	**167 542 037**	1	1.190	124	108	184	128	101	49	79	129

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com