




SYGEF Standard Ventilating and bleed valve type 591
With socket fusion spigots metric

Model:

- Material: PVDF
- With protection cap up to DN50 made of PP-GF, DN65-100 made of POM
- Special floater made of PVDF
- Designed for easy installation and removal
- Compact installation length

d	SDR	DN	PN	FKM	D	L	t	closest
(mm)		(mm)	(bar)	Code	(mm)	(mm)	(mm)	inch
16	21	10	16	175 591 031	50	135	13	3/8
20	21	15	16	175 591 032	50	140	14	1/2
25	21	20	16	175 591 033	58	157	16	3/4
32	21	25	16	175 591 034	68	168	18	1
40	21	32	16	175 591 035	84	189	20	1 1/4
50	21	40	16	175 591 036	97	211	23	1 1/2
63	21	50	16	175 591 037	124	245	27	2



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>