



COOL-FIT 2.0/4.0 Barrel nipple

Model:

- PE100, SDR11/17, metric
- For the shortest possible connection between fittings
- For media temperatures between 0°C up to 60°C
- COOL-FIT 2.0/4.0 Adhesive ring needed for joining

d	DN	SDR	PN	Code	Weight	z
(mm)	(mm)		(bar)		(kg)	(mm)
32	25	11	16	738 910 408	0.020	76
40	32	11	16	738 910 409	0.034	80
50	40	11	16	738 910 410	0.059	88
63	50	11	16	738 910 411	0.101	96
75	65	11	16	738 910 412	0.162	110
90	80	11	16	738 910 413	0.264	124
110	100	11	16	738 910 414	0.454	144
140	125	11	16	738 910 416	0.855	168
160	150	17	10	738 910 417	0.798	180
225	200	17	10	738 910 420	1.885	220

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>