




**ecoFIT Adaptor socket PE80**  
**d20-63mm / Female thread Rp**

**Model:**

- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- With fusion socket metric and parallel female thread Rp, reinforced
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes



| d    | Thread Type | Size   | DN   | SDR | PN    | Code               | Weight | Lmax | z    | SLW  |
|------|-------------|--------|------|-----|-------|--------------------|--------|------|------|------|
| (mm) |             | (inch) | (mm) |     | (bar) |                    | (kg)   | (mm) | (mm) | (mm) |
| 20   | Rp          | ½      | 15   | 11  | 10    | <b>733 910 206</b> | 0.020  | 35   | 7    | 32   |
| 25   | Rp          | ¾      | 20   | 11  | 10    | <b>733 910 207</b> | 0.026  | 39   | 7    | 36   |
| 32   | Rp          | 1      | 25   | 11  | 10    | <b>733 910 208</b> | 0.042  | 45   | 7    | 46   |
| 40   | Rp          | 1 ¼    | 32   | 11  | 10    | <b>733 910 209</b> | 0.068  | 53   | 7    | 55   |
| 50   | Rp          | 1 ½    | 40   | 11  | 10    | <b>733 910 210</b> | 0.098  | 54   | 9    | 65   |
| 63   | Rp          | 2      | 50   | 11  | 10    | <b>733 910 211</b> | 0.155  | 62   | 9    | 80   |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>