




329

Screwed flange, drilled, 4 holes

Diameter of pitch circle and sealing face compatible to EN 1092-2 and DIN 2566.
* 8 holes



	Dim. (inch)	PN (bar)	Black Code	Galvanised Code	SP	GP
EN *-	½	16	770 329 104	770 329 204	10	
EN *-	¾	16	770 329 105	770 329 205	10	
EN *-	1	16	770 329 106	770 329 206	5	
EN *-	1 ¼	16	770 329 107	770 329 207	10	
EN *-	1 ½	16	770 329 108	770 329 208	10	
EN *-	2	16	770 329 109	770 329 209	8	
EN *-	2 ½	16	770 329 110	770 329 210	6	
EN *-	3	10	770 329 111	770 329 211	4	
EN *-	3	16	770 329 115	770 329 215	4	
EN *-	4	16	770 329 112	770 329 212	3	

	Dim. (inch)	PN (bar)	a (mm)	b (mm)	d (mm)	k (mm)	z (mm)	H (mm)	D (mm)
EN *-	½	16	35	14	14	65	7	20	95
EN *-	¾	16	45	16	14	75	9	24	105
EN *-	1	16	52	17	14	85	7	24	115
EN *-	1 ¼	16	60	17	19	100	7	26	140
EN *-	1 ½	16	72	13	19	110	8	26	150
EN *-	2	16	87	16	19	125	5	29	165
EN *-	2 ½	16	100	16	19	145	5	32	185
EN *-	3	10	115	18	19	160	6	36	200
EN *-	3	16	115	18	19	160	6	36	200
EN *-	4	16	140	20	19	180	2	38	220

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>