# Data sheet

valid from: 4/2/26




**SYGEF Standard reducer**
**SDR33/PN10**

**Model:**

- Material: PVDF

| d (mm) | d1 (mm) | PN (bar) | SDR | FM | Code | Weight (kg) | L (mm) | L1 (mm) | L2 (mm) | e (mm) | e1 (mm) |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 90 | 63 | 10 | 33 | BCF, IR | **735 908 551** | 0.124 | 75 | 25 | 30 | 2.8 | 3.0 |
| 110 | 63 | 10 | 33 | BCF, IR | **735 908 553** | 0.196 | 90 | 30 | 30 | 3.4 | 3.0 |
| 110 | 90 | 10 | 33 | BCF, IR | **735 908 555** | 0.179 | 90 | 30 | 35 | 3.4 | 2.8 |
| 125 | 110 | 10 | 33 | IR | **735 908 580** | 0.270 | 100 | 35 | 40 | 3.9 | 5.3 |
| 140 | 110 | 10 | 33 | IR | **735 908 585** | 0.385 | 110 | 40 | 40 | 4.3 | 5.3 |
| 140 | 125 | 10 | 33 | IR | **735 908 584** | 0.340 | 110 | 40 | 40 | 4.3 | 3.9 |
| 160 | 110 | 10 | 33 | IR | **735 908 561** | 0.480 | 120 | 40 | 40 | 4.9 | 3.4 |
| 160 | 110 | 10 | 33 | IR | **735 908 590** | 0.573 | 120 | 40 | 40 | 4.9 | 5.3 |
| 160 | 140 | 10 | 33 | IR | **735 908 588** | 0.568 | 120 | 40 | 40 | 4.9 | 4.3 |
| 200 | 160 | 10 | 33 | IR | **735 908 592** | 0.830 | 145 | 50 | 40 | 6.2 | 4.9 |
| 225 | 110 | 10 | 33 | IR | **735 908 566** | 1.120 | 160 | 55 | 35 | 6.9 | 3.4 |
| 225 | 110 | 10 | 33 | IR | **735 908 595** | 0.940 | 160 | 55 | 35 | 6.9 | 5.3 |
| 225 | 160 | 10 | 33 | IR | **735 908 596** | 1.140 | 160 | 55 | 40 | 6.9 | 4.9 |
| 225 | 200 | 10 | 33 | IR | **735 908 597** | 1.200 | 160 | 55 | 50 | 6.9 | 6.2 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com