



COOL-FIT 4.0 Barrel nipple with insulation, d32-d225

Model:

- Pre-insulated PE100 SDR11/17 metric
- Insulation made from GF HE foam
- Impact resistant. Color: black
- For short connections between COOL-FIT 4.0 Fittings Typ A

d (mm)	D (mm)	DN (mm)	SDR	PN (bar)	Code	Weight (kg)	L1 (mm)	z (mm)
32	90	25	11	16	738 913 408	0.126	36	151
40	110	32	11	16	738 913 409	0.188	40	155
50	110	40	11	16	738 913 410	0.226	44	163
63	125	50	11	16	738 913 411	0.328	48	171
75	140	65	11	16	738 913 412	0.447	55	185
90	160	80	11	16	738 913 413	0.631	62	199
110	180	100	11	16	738 913 414	0.929	72	219
140	225	125	11	16	738 913 416	1.101	84	243
160	250	150	17	10	738 913 417	1.576	90	255
225	315	200	17	10	738 913 420	3.254	110	295

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>