




ecoFIT Adaptor nipple PE100
d20-63mm / SDR11 / Male thread R

Model:

- With butt fusion spigot SDR11 and tapered male thread
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes



d	Thread Type	Size	DN	PN	SDR	FM	Code	Weight	Lmax	s1	SLW	Bm1
(mm)		(inch)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)
20	R	½	15	16	11	IR	753 910 556	0.013	51	1.9	32	23
25	R	¾	20	16	11	IR	753 910 557	0.026	52	2.3	36	23
32	R	1	25	16	11	IR	753 910 558	0.028	55	3.0	46	23
40	R	1 ¼	32	16	11	IR	753 910 559	0.043	58	3.7	55	23
50	R	1 ½	40	16	11	IR	753 910 560	0.063	60	4.6	65	23
63	R	2	50	16	11	IR	753 910 561	0.104	67	5.8	80	26

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>