




COOL-FIT 2.0 Weld-in port PE/brass With female thread Rp

Model:

- Material: PE100, brass with low lead content, dezincification resistant
- With Weld-in port cone (PE100) and female thread Rp (brass) for the installation of sensors, instruments, venting and draining
- Gasket: O-ring EPDM
- Including insulation made from EPDM foam

Note:

For pipes COOL-FIT 2.0, COOL-FIT 2.0F, COOL-FIT 4.0 and COOL-FIT 4.0F of the dimension d63-d225



Size (inch)	Thread	PN (bar)	Code	Weight (kg)	d (mm)	db1 (mm)	D1 (mm)	h1 (mm)	P1 (mm)	z (mm)
½	Rp	16	738 114 106	0.140	d63 - d225	11.8	73	85+d/2	15	70+d/2
¾	Rp	16	738 114 107	0.183	d63 - d225	17.4	73	85+d/2	16	69+d/2
1	Rp	16	738 114 108	0.247	d63 - d225	23.1	73	85+d/2	19	67+d/2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>